

SLIM LED



- FEATURES :**
- Slimline linear LED system
 - Sections plug together for continuous lighting with no visible dark spots
 - Remote 24V DC power pack is required
 - Ideal for concealed lighting applications such as jewellery stores, retail displays, under cabinets, halo style lighting in ceiling coves & above or within pelmets
 - Maximum single run is 7.76m=96W (expect 5% light loss over max. length)
 - Mounting via supplied surface clips

- EXTRAS :**
- Connector Cable 300mm (SLED-LINK300)
 - Connector Cable 1200mm(SLED-LINK1200)
 - 25W Remote Driver (SLED-D-25WDC)
 - 100W Remote Driver (LCU100-24DC)

CODE

SLED03W-3K-6
SLED03W-4K-6
SLED06W-3K-6
SLED06W-4K-6
SLED09W-3K-6
SLED09W-4K-6
SLED12W-3K-6
SLED12W-4K-6

WATTAGE

3W
3W
6W
6W
9W
9W
12W
12W

COLOUR TEMPERATURE

3000K
4000K
3000K
4000K
3000K
4000K
3000K
4000K

DIMENSIONS

250mm x 12mm x 17mm
250mm x 12mm x 17mm
490mm x 12mm x 17mm
490mm x 12mm x 17mm
730mm x 12mm x 17mm
730mm x 12mm x 17mm
970mm x 12mm x 17mm
970mm x 12mm x 17mm