






## **35 DEGREE**





## FEATURES: •

- Australian designed & manufactured surface mounted low glare accent downlight
- Extruded aluminium body
- Suitable for concrete slab mounting, solid or plasterboard ceilings
- LED lamp / PAR16 LED GU10 240V, offers various lamp options
- Fixed or adjustable 40° tilt
- Lumen options up to 750lm
- No remote driver required
- Dimmable
- COB / 12V MR16 versions available with remote driver
- Serviceable IP20 downlight
- Ideal for residential / hospitality / gallery / museum & commercial applications
- IES files available on request

COLOURS:	Black	-2
	White	-3
	Silver	-6
	Custom	-5

## **ACCESSORIES:**

- Deco glass filter holder (CHL)
- Frosted glass 30mm (FG)
- Deco colour glass 50mm (DG)
- Honeycomb filter (AL 20)

BSM11 (fixed)	BSM12 (adjustable)			
	165mm		165mm	
100mm		100mm		

CODE	LAMP TYPE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	DIMENSIONS
BSM11-Fixed	PAR16	8.5W	660/670/680	2700K/3000K/4000K	35°	80/90/90	165mm x 100mm diameter
BSM12-Adj	PAR16	8.5W	660/670/680	2700K/3000K/4000K	35°	80/90/90	165mm x 100mm diameter

www.massonforlight.com.au email: sales@massonforlight.com.au