


## MONDO COB TRIMLESS- PRO

- FEATURES:**
- Australian designed & manufactured professional recessed low glare accent LED downlight
  - Adjustable 45° tilt, 359° rotation
  - Lumen options 980lm up to 1510lm / CRI 80 / CRI 90
  - Requires remote electronic driver.
  - Specify - Non dim / Phase-cut dim / Dali dim
  - Dali - Smart phone blue tooth connectivity available on request
  - Dali dim 100% - 0.1% option available on request
  - Casambi Bluetooth wireless mesh control system available on request
  - Colour temps available: 2700k/3000k/4000k/6500k
  - Serviceable IP20 downlight
  - Ideal for commercial / hospitality / retail / gallery / museum / residential / applications
  - IES files available on request


**TRIM COLOURS:**

Black	-2	Inner standard as Black
White	-3	
White	-3-3	
Silver	-6	
Custom	-5	

- ACCESSORIES:**
- Deco glass filter holder (CHL)
  - Frosted glass 30mm (FG)
  - Deco colour glass 50mm (DG)
  - AL 20 HoneyComb filter



### 40 DEGREE




CODE	LAMP TYPE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	mA	DIMENSIONS
MTL501	COB	1x 12.3	980	3000K	15,24,40	90	350	UNO 118mm height cutout - 106mm x 106mm
MTL502	COB	2x 12.3	1960	3000K	15,24,40	90	350	DUO 118mm height cutout - 106mm x 206mm
MTL503	COB	3x 12.3	2940	3000K	15,24,40	90	350	TRIO 118mm height cutout - 106mm x 307mm
MTL505	COB	4x 12.3	3920	3000K	15,24,40	90	350	QUATRO SQ 118mm height cutout - 206mm x 206mm

**PROFESSIONAL**


CODE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	MA
MC50-COB-900-927-15D-G1	12.3	980	2700k	15	90	350
MC50-COB-900-927-24D-G1	12.3	960	2700k	24	90	350
MC50-COB-900-927-40D-G1	12.3	920	2700k	40	90	350
MC50-COB-900-930-15D G1	12.3	1040	3000K	15	90	350
MC50-COB-900-930-24D G1	12.3	1020	3000K	24	90	350
MC50-COB-900-930-40D G1	12.3	980	3000K	40	90	350
MC50-COB-900-940-15D G1	12.3	1120	4000K	15	90	350
MC50-COB-900-940-24D G1	12.3	1090	4000K	24	90	350
MC50-COB-900-940-40D G1	12.3	1050	4000K	40	90	350
MC50-COB-1400-930-24D G1	12.9	1430	3000K	24	80	350
MC50-COB-1400-930-40D G1	12.9	1360	3000K	40	80	350
MC50-COB-1400-940-24D G1	12.9	1510	4000K	24	80	350
MC50-COB-1400-940-40D G1	12.9	1430	4000K	40	80	350

- Color consistency Mac Adam Step: 3 (<3SDCM)
- High color rendering performance, CRI 80 and 90 (TM30 compliant) IES TM30


**15 DEGREE**



**24 DEGREE**



**40 DEGREE**



**DRIVER OPTIONS:**

- OTI / Dali dimmable
- OTE / PhaseCut
- OT / Non dimmable