

## MONDO 111 COB TRIMLESS - PRO

### FEATURES:

- Australian designed & manufactured professional large recessed low glare accent LED downlight
- Adjustable 40° tilt, 359° rotation
- Lumen options 1800 up to 4780lm / CRI 80 / CRI 90
- Requires remote electronic driver.
- Specify - Non dim / Phase-cut dim / Dali dim
- Dali - Smart phone blue tooth connectivity available on request
- Dali dim 100% - 0.1% option available on request
- Casambi Bluetooth wireless mesh control system available on request
- Colour temps available: 2700k/3000k/4000k
- Serviceable IP20 downlight
- Ideal for commercial / hospitality / retail / gallery / museum / residential applications
- IES files available on request

### TRIM



### COLOURS:

	Black	-2	Inner standard as Black
	White	-3	
	White	-3-3	
	Silver	-6	
	Custom	-5	

### ACCESSORIES:

- Deco glass filter holder (CHL)
- Frosted glass 30mm (FG)
- Deco colour glass 50mm (DG)
- AL 20 HoneyComb filter

### 40 DEGREE




CODE	LAMP TYPE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	mA	DIMENSIONS
MTL611	COB	1x 18	1800	3000K	15,24,40	90	500	UNO 120mm depth cutout - 171mm x 171mm
MTL612	COB	2x 18	3600	3000K	15,24,40	90	500	DUO 120mm depth cutout -171mm x 331mm
MTL613	COB	3x 18	5400	3000K	15,24,40	90	500	TRIO 120mm depth cutout - 171mm x 491mm
MTL615	COB	4x 18	7200	3000K	15,24,40	90	500	QUATRO 120mm depth cutout - 341mm x 341mm

**PROFESSIONAL**


CODE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	MA
MC111-COB-1800-927-15D-G1	18	1730	2700	15	90	500
MC111-COB-1800-927-24D-G1	18	1770	2700	24	90	500
MC111-COB-1800-927-40D-G1	18	1770	2700	40	90	500
MC111-COB-1800-930-15D-G1	18	1840	3000	15	90	500
MC111-COB-1800-930-24D-G1	18	1880	3000	24	90	500
MC111-COB-1800-930-40D-G1	18	1800	3000	40	90	500
MC111-COB-1800-940-15D-G1	18	1940	4000	15	90	500
MC111-COB-1800-940-24D-G1	18	1990	4000	24	90	500
MC111-COB-1800-940-40D-G1	18	1910	4000	40	80	500
MC111-COB-2800-830-15D-G1	25.9	2700	3000	15	80	700
MC111-COB-2800-830-24D-G1	25.9	2760	3000	24	80	700
MC111-COB-2800-830-40D-G1	25.9	2650	3000	40	80	700
MC111-COB-2800-840-15D-G1	25.9	2830	4000	15	80	700
MC111-COB-2800-840-24D-G1	25.9	2900	4000	24	80	700
MC111-COB-2800-840-40D-G1	25.9	2780	4000	40	80	700
MC111-COB-4300-830-24D-G1	37.6	4550	3000	24	80	1050
MC111-COB-4300-830-40D-G1	37.6	4340	3000	40	80	1050
MC111-COB-4300-830-60D-G1	37.6	4240	3000	60	80	1050
MC111-COB-4300-840-24D-G1	37.6	4780	4000	24	80	1050
MC111-COB-4300-840-40D-G1	37.6	4560	4000	40	80	1050
MC111-COB-4300-840-60D-G1	37.6	4450	4000	60	80	1050

- Color consistency Mac Adam Step: 3 (<3SDCM)
- High color rendering performance, CRI 80 and 90 (TM30 compliant) IES TM30


**15 DEGREE**



**24 DEGREE**



**40 DEGREE**



**DRIVER OPTIONS:**

- OTI / Dali dimmable
- OTE / PhaseCut
- OT / Non dimmable