

## PEBBLE COB - PRO

- FEATURES:**
- Australian designed & manufactured professional recessed low glare accent LED downlight
  - Adjustable 20° two way tilt
  - Lumen options 980lm up to 1510lm / CRI 80 / CRI 90
  - Requires remote electronic driver.
  - Specify - Non dim / Phase-cut dim / Dali dim
  - Dali - Smart phone blue tooth connectivity available on request
  - Dali dim 100% - 0.1% option available on request
  - Casambi Bluetooth wireless mesh control system available on request
  - Colour temps available: 2700k/3000k/4000k
  - Serviceable IP20 downlight
  - Ideal for commercial / hospitality / retail / gallery / museum / residential applications
  - IES files available on request



**TRIM COLOURS:**

■	Black	-2	Inner standard as Black
□	White	-3	
□	White	-3-3	
■	Silver	-6	
■	Custom	-5	

- ACCESSORIES:**
- Deco glass filter holder (CHL)
  - Frosted glass 30mm (FG)
  - Deco colour glass 50mm (DG)
  - AL 20 honeycomb filter



### 40 DEGREE




CODE	LAMP TYPE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	mA	DIMENSIONS
PEB501	COB	12.3W	980	3000K	15,24,40	90	350	Approx 130mm dia x 80mm height cutout 95mm diameter
PEB502	COB	12.3W	1960	3000K	15,24,40	90	350	Approx 130mm dia x 80mm height cutout 95mm diameter
PEB503	COB	12.3W	2940	3000K	15,24,40	90	350	Approx 130mm dia x 80mm height cutout 95mm diameter

**PROFESSIONAL**


CODE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	MA
MC50-COB-900-927-15D-G1	12.3	980	2700k	15	90	350
MC50-COB-900-927-24D-G1	12.3	960	2700k	24	90	350
MC50-COB-900-927-40D-G1	12.3	920	2700k	40	90	350
MC50-COB-900-930-15D G1	12.3	1040	3000K	15	90	350
MC50-COB-900-930-24D G1	12.3	1020	3000K	24	90	350
MC50-COB-900-930-40D G1	12.3	980	3000K	40	90	350
MC50-COB-900-940-15D G1	12.3	1120	4000K	15	90	350
MC50-COB-900-940-24D G1	12.3	1090	4000K	24	90	350
MC50-COB-900-940-40D G1	12.3	1050	4000K	40	90	350
MC50-COB-1400-930-24D G1	12.9	1430	3000K	24	80	350
MC50-COB-1400-930-40D G1	12.9	1360	3000K	40	80	350
MC50-COB-1400-940-24D G1	12.9	1510	4000K	24	80	350
MC50-COB-1400-940-40D G1	12.9	1430	4000K	40	80	350

- Color consistency Mac Adam Step: 3 (<3SDCM)
- High color rendering performance, CRI 80 and 90 (TM30 compliant) IES TM30


**15 DEGREE**



**24 DEGREE**



**40 DEGREE**



**DRIVER OPTIONS:**

- OTI / Dali dimmable
- OTE / PhaseCut
- OT / Non dimmable