



## ROMAN LED PENDANT

- FEATURES:**
- Australian designed & manufactured professional low glare, down only pendant
  - Linear LED pendant lighting system, surface mounted and wall options available on request
  - Extruded aluminium profile
  - Fixed beam angle 140°
  - Higher lumen options available on request
  - (Mac Adam 3), CRI 90
  - No external power cable required (low voltage power runs down suspension wires)
  - Single power cable is required to run back to one end through the ceiling cavity
  - External power cable one end available on request for solid ceilings
  - Surface mounted driver box available on request for solid ceilings
  - Additional suspension cable required for pendants over 2m in length
  - Remote 24v constant voltage driver
  - Non dim standard or specify - Phase-cut, 0-10v, Dali dim, Casambi on request
  - Custom options available on request.
  - Custom lengths available from 1m to 9m
  - Serviceable IP20 pendant
  - Available in various colour temperatures 2700k, 3000k, 4000k
  - Ideal for residential, hospitality and commercial applications
  - IES files available on request

- COLOURS:**
- Black -2
  - White -3
  - Silver -6
  - Bronze -7



CODE	WATTAGE	LUMENS	COLOUR TEMP	BEAM ANGLE	CRI	DIMENSIONS
ROM1500	29W	3038lm	3000K / 4000K	140	90	1500mm x 25mm x 40mm - 3000mm drop (max)
ROM2160	42W	4859lm	3000K / 4000K	140	90	2160mm x 25mm x 40mm - 3000mm drop (max)
ROM2500	50W	5288lm	3000K / 4000K	140	90	2500mm x 25mm x 40mm - 3000mm drop (max)
ROM3000	60W	6413lm	3000K / 4000K	140	90	3000mm x 25mm x 40mm - 3000mm drop (max)