









40 DEGREE BEAM ANGLE AS STANDARD SPEC OPTIONS BELOW







TULLYSPOT RETRACTABLE COB - PRO

FEATURES: •

- Australian designed & made professional recessed ultra-low glare accent COB downlight with retractable spotlight.
- An adjustable downlight, spotlight or wall washer in
- Adjustable vertical axis and pivot up 45°, 359° swivel
- Lumen options 980lm up to 1400lm/CRI 90
- Requires remote electronic driver
- Specify Non-dim/Phase-cut dim/Dali dim/Casambi
- Dali Smart phone Bluetooth connectivity available on request
- Dali dim 100% 0.1% option available on request.
- Casambi Bluetooth wireless mesh control system available on request
- Mac Adam step 2
- Serviceable IP20 spotlight
- Colour temps available: 2700k / 3000k / 4000k
- Ideal for commercial / hospitality / retail / gallery / museum / residential applications
- IES files available on request.

| COLOURS: | | Black | -2 |
|----------|----|--------|----|
| | | White | -3 |
| | | Silver | -6 |
| | A. | Bronze | -7 |
| | | Brass | -8 |
| | | Custom | -5 |
| | | | |

ACCESSORIES:

- Deco glass filter holder (CHL)
- Frosted glass 30mm (FG)
- Deco colour glass 50mm (DG)
- Honeycomb filter (AL20)
- Mited snoot / 140mm UP (TBC)
- Mited snoot / 140mm Down (TBC)

| CODE | LAMP TYPE | WATTAGE | LUMENS | COLOUR TEMP | BEAM° | CRI | mA | DIMENSIONS |
|------------|-----------|---------|--------|-------------|-------|-----|-----|--|
| TUM501/225 | COB | 9 | 980 | 3000K | 24,40 | 90 | 225 | 100mm length x 54mm diameter - 83mm diameter cut-out - 160mm deep |
| TUM511/350 | СОВ | 12.3 | 1335 | 3000K | 24,40 | 90 | 350 | 100mm length x 54mm diameter - 83mm diameter cut-out - 160mm deep |

www.massonforlight.com.au

email: sales@massonforlight.com.au




PROFESSIONAL

TO SPECIFY ADDITIONAL LED MODULE. "LAMP" OPTIONS: PLEASE SELECT FROM THE CODES BELOW AND ADD TO THE SPECIFICATION


| CODE | WATTAGE | LUMENS | COLOUR TEMP | BEAM ANGLE | CRI | MA |
|--------------------------|---------|--------|-------------|------------|-----|-----|
| MC50-COB-900-927-24D-G2 | 9 | 960 | 2700k | 24 | 90 | 225 |
| MC50-COB-900-927-40D-G2 | 9 | 920 | 2700k | 40 | 90 | 225 |
| MC50-COB-900-930-24D G2 | 9 | 1020 | 3000K | 24 | 90 | 225 |
| MC50-COB-900-930-40D G2 | 9 | 980 | 3000K | 40 | 90 | 225 |
| MC50-COB-900-940-24D G2 | 9 | 1090 | 4000K | 24 | 90 | 225 |
| MC50-COB-900-940-40D G2 | 9 | 1050 | 4000K | 40 | 90 | 225 |
| MC50-COB-1400-930-24D G2 | 12.9 | 1220 | 3000K | 24 | 90 | 350 |
| MC50-COB-1400-930-40D G2 | 12.9 | 1270 | 3000K | 40 | 90 | 350 |
| MC50-COB-1400-940-24D G2 | 12.9 | 1305 | 4000K | 24 | 90 | 350 |
| MC50-COB-1400-940-40D G2 | 12.9 | 1335 | 4000K | 40 | 90 | 350 |

- Color consistency Mac Adam Step: 2 (<2SDCM)
- High color rendering performance, CRI 90 (TM30 compliant) IES TM30

24 DEGREE



40 DEGREE



DRIVER OPTIONS: . OTI / Dali dimmable

OTFIT / PhaseCut